

mesh opening (micron)	mesh count mesh/cm	weave	thread diam.(micron)	open surface (%)	thickness (micron)	weight (g/m ²)
1950	4	PW	550	61	950	262
1500	5	PW	500	56	850	271
1267	6	PW	400	58	780	208
1079	7	PW	350	57	675	186
900	8	PW	350	52	685	212
860	9	PW	250	60	455	145
700	10	PW	300	49	576	195
583	12S	PW	250	49	470	162
533	12	PW	300	41	585	234
414	14	PW	300	34	595	273
425	16S	PW	200	46	370	139
375	16	PW	250	36	485	217
350	20S	PW	150	49	375	98
300	20	PW	200	36	385	173
267	24	PW	150	41	285	117
237	28	PW	120	44	215	87
213	30	PW	120	41	225	94
213	32	PW	100	46	165	69
195	34	PW	100	43	170	73
178	36	PW	100	41	178	78
150	40	PW	100	36	190	87
152	43	PW	80	43	135	60
130	48	PW	80	38	145	62
120	56	PW	60	44	85	44
110	59	PW	60	42	98	46
100	64	PW	60	37	105	50
90	72	PW	50	41	82	39
75	80	PW	50	36	90	43
60	100	PW	40	36	65	35
63	90	PW	50	31	96	48
43	120	PW	40	25	70	42
37	130	PW	40	23	75	45

Top Zeven b.v.

Wateringweg 34, 2031 EJ Haarlem, Netherlands,
tel +31(0)23 5319051, fax +31(0)23 5319065
filter@topzeven.com , www.topzeven.com